

Real-time monitoring for
peace of mind

MOCREO.COM

TALK TO US


+1 (530) 988-8608
help@mocreo.com

SELECTION GUIDE

for MOCREO Monitoring Products

Thank you for choosing MOCREO! Your trust is the greatest honor we've earned in our 15 years of dedication to smart home innovation. What you've entrusted to us isn't just an order—it's your vision of a better, more connected life—and we're proud to support it with three carefully designed product lines!

SMALL AREA




Monitoring multiple points in garage or kitchen? The Bluetooth Low Energy (BLE) Sensors + Hub combinations are **cost-effective**. Coverage range up to **130 feet**.

For larger spaces like houses or buildings, our **LoRa Sensors + Hub** offer reliable coverage up to **1640 feet**, ensuring strong, comprehensive monitoring.

LARGE AREA



STANDALONE DEPLOYMENT



Need to monitor a single fridge or specific spot? Choose our **Wi-Fi/4G series** — **no hub** required for fast and easy setup.

Environmental Monitoring
for Peace of Mind

Read More at
mocreo.com

BLE SENSORS for SMALL AREA

Each BLE sensor **runs on a battery for over 2 years**, making deployment easy. One hub covers up to 30 sensors **within 130 feet**, and adding more hubs extends the range. BLE Hubs connect to MOCREO Cloud via Wi-Fi or Ethernet, with real-time alerts sent to your phone.

Temperature Only

Model	Features
ST5	<ul style="list-style-type: none">External temperature <u>probe</u>Temp range: -40°F to 221°FAccuracy: ±0.9°F (within the range of 14°F to 185°F)Built-in <u>rechargeable</u> 1800mAh batteryCompatible Apps: MOCREO Sensor App, MOCREO Smart AppIdeal for freezers, refrigerators, hot tubs, boilers and more
MS1	<ul style="list-style-type: none">An enhanced version of the ST5, including all its features, plus:Battery: 3 × AAA (<u>replaceable</u>)Easy installation with included Velcro or a hanging loopCompact size for flexible placement
ST8	<ul style="list-style-type: none">Shares features with ST5, plus:Battery: 1 × 6LR61 (<u>replaceable</u>)Built-in 120dB <u>loud beeper</u><u>Data logger</u> records 32,000 temp readingsConnects to your phone via <u>BLE directly</u>, or works with a hub for remote monitoring
ST10	<ul style="list-style-type: none">Shares features with ST5, plus:Ultra-wide temp measuring range: -328 to 392°F (±1.8°F)External PT100 platinum resistance temperature probeIdeal for labs, medical vaccine refrigerators, cryogenic freezers, pharmacy refrigerators, blood bank freezers, biological safety cabinets, and more

BLE SENSORS for SMALL AREA

Temperature + Humidity

Model	Features
ST6	<ul style="list-style-type: none"><u>Built-in</u> high-precision sensors from SensirionTemp range: -4 to +140°FHumidity range: 0 to 100%RHAccuracy: ±2% (from 10–90% RH), ±4% (for 0–10% & 90–100% RH)Built-in rechargeable 1800mAh battery lasts up to <u>2 years</u> per full chargeCompatible Apps: MOCREO Sensor App, MOCREO Smart AppPerfect for houses, greenhouses, storage areas, cabins, attics, crawl spaces, server rooms.
ST9	<ul style="list-style-type: none"><u>External</u> IP67 waterproof <u>probe</u>Temp range: -40 to +221°FHumidity range: 0 to 100%RHAccuracy: ±2% (from 10–90% RH), ±4% (for 0–10% & 90–100% RH)Built-in rechargeable 1800mAh battery lasts up to <u>2 years</u> per full chargeCompatible Apps: MOCREO Sensor App, MOCREO Smart AppPerfect for snake tanks, geckos, lizards, crawl spaces, turtle habitats, greenhouses, and other high-humidity environments

Water Leakage

SW2	<ul style="list-style-type: none">Dual Alarm States: Water Detected / No WaterBuilt-in <u>95dB loud beeper</u>Built-in rechargeable 1800mAh battery lasts up to <u>2 years</u> per full chargeCompatible Apps: MOCREO Sensor App, MOCREO Smart AppSuitable for kitchen, bathroom, washing machine, basement, fish tank, pump room, water heater, boiler bottom, HVAC, air conditioning drain pipe
-----	---

Don't Let a Drip Become a Disaster

BLE SENSORS for SMALL AREA

BLE Hubs for Small Area

Model	Features
H1	<ul style="list-style-type: none">2.4GHz <u>Wi-Fi</u> + 100Mbps <u>Ethernet</u> connectivityExternal BLE antenna for extended rangePowered via external 5V DC adapterOnly works with <u>MOCREO Sensor App</u>
H3	<ul style="list-style-type: none">2.4GHz <u>Wi-Fi</u> connectivityBuilt-in BLE antenna<u>Plug-in design</u> with integrated power supplyRemote control power output switchUpgraded replacement for the H2 HubOnly works with <u>MOCREO Smart App</u>
H5Lite	<ul style="list-style-type: none">2.4GHz <u>Wi-Fi</u> connectivityBuilt-in BLE antennaLCD <u>Screen</u> displays sensor dataLED Segment display for sensor data or clockOptional external probe to direct temperature measurementOnly works with <u>MOCREO Smart App</u>

All BLE sensors work with all MOCREO hubs, including both BLE and LoRa models.

For any BLE sensor,

- If connected via **H1, H2**(obsoleted), it can only be managed using the **MOCREO Sensor App**.
- If connected via **H3, H5Lite, H5Pro, H6Lite or H6Pro**, it can only be managed using the **MOCREO Smart App**.

Sensor App vs. Smart App

The **MOCREO Smart App** is built with our latest cloud platform. We recommend all users migrate from the **MOCREO Sensor App** to the **Smart App**.

We Apologize for Any Confusion Caused by Product Updates!



MOCREO.COM

TALK TO US

+1 (530) 988-8608
help@mocreo.com

LoRa SENSORS for LARGE AREA

Each sensor runs on battery for over 2 years, making deployment easy. One hub covers 100+ sensors within **1640 feet**, and adding more hubs extends range. Hubs connect to MOCREO Cloud via Wi-Fi or Ethernet, with real-time alerts sent to your phone.

All LoRa sensors work exclusively with LoRa Hubs (H5Pro or H6Pro) and are only compatible with the MOCREO Smart App.

Temperature Only

Model	Features
LS1	<ul style="list-style-type: none">Built-in temperature sensor allows placing the <u>entire device in a freezer</u> — no cables requiredTemperature range: -20 to +131°F (±0.9°F)Battery: 3 × AAA (<u>replaceable</u>)IP66 waterproofIdeal for most freezers and refrigerators
LS2	<ul style="list-style-type: none">External IP67 waterproof temperature <u>probe</u>Wide temp range: -40 to +221°F (±0.9°F)Accuracy: ±0.9°F (within the range of 14°F to 185°F)Battery: 3 × AAA (<u>replaceable</u>)Main body stays outside the freezer for better signal transmissionIdeal for low-temperature freezers, refrigerators, hot tubs, boilers, and more
LS4	<ul style="list-style-type: none">Pool ThermometerTemperature range: -4 to +158°F (±0.9°F)Battery: 3 × AAA(<u>replaceable</u>)IP67 waterproofIdeal for swimming pools, paddling pools, hot tubs, fish ponds, jacuzzis, spas, and more

LoRa SENSORS for LARGE AREA

Temperature + Humidity

Model	Features
LS3	<ul style="list-style-type: none"><u>Built-in</u> high-precision sensors from SensirionTemp range: -4 to +140°F (±0.5°F)Humidity range: 0 to 100% RHAccuracy: ±2% RH (10–90%), ±3% RH (0–10% / 90–100%)Battery: 3 × AAA (<u>replaceable</u>)Perfect for houses, greenhouses, storage areas, cabins, attics, crawl spaces, server rooms, and more.

Water Leakage

LW1	<ul style="list-style-type: none">All-in-one detectorDetects: Dry / Drip / Wet / FloodBuilt-in temp sensor for freeze risk prediction110 dB alarm with night-time low volume modeIP67 waterproofBattery: 2 × AAA (<u>replaceable</u>)
LW2	<ul style="list-style-type: none">External water leak cableLong cable expands the leak detection coverageBattery: 3 × AAA (<u>replaceable</u>)Ideal for kitchens/bathrooms, data centers/server rooms, commercial buildings/basements, and more

**Smart Sensing.
Dry Living.**

PEACE OF MIND

LoRa SENSORS for LARGE AREA

Security

Model	Features
LD2	<ul style="list-style-type: none">Outdoor contact sensorOperating temperature range of 14–140°FIP67 waterproofBattery: 2 × AA (<u>replaceable</u>)Ideal for gate and shed door status detection
LD3	<ul style="list-style-type: none">Mailbox opening alert sensorOperating temperature range of 14–140°FIP65 waterproofBattery: 2 × AA (<u>replaceable</u>)
LB1	<ul style="list-style-type: none">Siren and Light Alarm120 dB alarm with night-time low volume modeUse it as an alarm for intrusion/burglar alarm, water leaks and high or low temperature and humidity

LoRa Hubs for Large Area

H5Pro	<ul style="list-style-type: none">2.4GHz <u>Wi-Fi</u> + 100Mbps <u>Ethernet</u> connectivityExternal LoRa antenna for extended rangeBuilt-in BLE antennaLCD <u>Screen</u> displays sensor dataLED Segment display for sensor data or clockPowered via external 5V DC adapter
H6Pro	<ul style="list-style-type: none">2.4GHz <u>Wi-Fi</u> connectivityBuilt-in LoRa & BLE antennaPlug-style design with integrated power supplyBuilt-in 80dB <u>beeper</u>LED night light with motion detection

All MOCREO LoRa hubs are equipped with BLE capability and are compatible with any MOCREO BLE sensor.

Wi-Fi/4G Devices for STANDALONE DEPLOYMENT

Each device connects to MOCREO Cloud via Wi-Fi or 4G, with real-time alerts sent to your phone.

Temperature Only

Model	Features
NS1	<ul style="list-style-type: none">2.4GHz <u>Wi-Fi</u> connectivityExternal temperature probeTemp range: -40 to +221°F (±0.9°F)Powered via external 5V DC adapterCompatible Apps: MOCREO Smart AppIdeal for freezers, refrigerators, fish tank, aquarium, hot tubs, boilers and more

Temperature Controller

ST7CL	<ul style="list-style-type: none">Temp Measuring Range -40°F--+221°FAccuracy: ±0.9°F (within the range of 14°F to 185°F)Automatically switches the power outlet on/offSet custom temperature thresholds80 dB loud alarmBluetooth Connection, 50ftCompatible Apps: MOCREO Sensor AppIdeal for home brewing, reptile tanks, terrarium heat lamps, aquarium heaters, seedling heating mats, greenhouses, incubators and more
-------	--

Networking Monitoring

NM2	<ul style="list-style-type: none">Automatic Network Monitoring & RebootInstant email notifications when the network goes downRemotely switch the power outlet on/off
-----	--

Wi-Fi/4G Sensors and Cameras, coming soon!